

In re Patent Application of:
BORGATTI ET AL.
Serial No. **10/798,401**
Filed: **JANUARY 30, 2004**

In the Claims:

Claims 1-9 (Cancelled).

10. (Currently Amended) A dynamically reconfigurable processing unit comprising:

a system bus;

a microprocessor coupled to said system bus;

at least one coprocessor coupled to said system bus;

an embedded Flash memory for non-volatile storage of code, data and bit-streams, said embedded Flash memory comprising a field programmable gate array (FPGA) port;

a direct memory access (DMA) channel; and

an SRAM ~~S-RAM~~ embedded FPGA ~~for FPGA reconfigurations,~~
~~said S-RAM embedded FPGA~~ comprising

an FPGA programming interface connected to the FPGA port of said embedded Flash memory through said DMA channel,

an instruction extension interface for extending a datapath of said microprocessor for supporting a set of additional microprocessor instructions,

a master/slave interface for supporting said at least one coprocessor, and

an input/output interface for interfacing with external sensors with application-specific

In re Patent Application of:

BORGATTI ET AL.

Serial No. **10/798,401**

Filed: **JANUARY 30, 2004**

communication protocols;

said microprocessor, said at least one coprocessor,
said system bus, said embedded Flash memory, said DMA channel and
said SRAM ~~S-RAM~~ embedded FPGA being integrated as a single chip.

11. (Previously Presented) A dynamically reconfigurable processing unit according to Claim 10, wherein said embedded Flash memory further comprises a code port and a data port; and wherein said DMA channel handles bit-stream transfers while said microprocessor fetches instructions and data from the code and data ports.

12. (Previously Presented) A dynamically reconfigurable processing unit according to Claim 10, wherein said embedded Flash memory comprises:

a modular array structure comprising N memory modules;

a power memory arbiter (PMA); and

a charge pump connected to said PMA and being shared among said N memory modules.

Claim 13 (Cancelled).

14. (Previously Presented) A dynamically reconfigurable processing unit according to Claim 11, wherein the code port of said embedded Flash memory is for optimizing random

In re Patent Application of:
BORGATTI ET AL.
Serial No. **10/798,401**
Filed: **JANUARY 30, 2004**

access time and an application system supported by the reconfigurable processing unit; the data port of said embedded Flash memory is for allowing access to application data for modification thereof; and the FPGA port of said embedded Flash memory is for providing serial access for downloading the bit-streams for an embedded FPGA configuration.

15. (Previously Presented) A dynamically reconfigurable processing unit according to Claim 11, wherein the FPGA port of said embedded Flash memory comprises four configuration registers replicating information stored in the code port to be used for writing data for embedded FPGA configurations.

16. (Previously Presented) A dynamically reconfigurable processing unit according to Claim 14, wherein the FPGA port uses a chip select signal to access addressable memory space, and a burst enable signal to allow burst serial access.

17. (Previously Presented) A dynamically reconfigurable processing unit according to Claim 10, further comprising a system bus connected to said DMA channel and said embedded Flash memory.

18. (Previously Presented) A dynamically reconfigurable processing unit according to Claim 14, wherein

In re Patent Application of:
BORGATTI ET AL.
Serial No. 10/798,401
Filed: **JANUARY 30, 2004**

said embedded Flash memory comprises four modules, each module being arranged in at least three programmable user-defined partitions, with each partition being dedicated to a corresponding port.

19. (Currently Amended) A reconfigurable processing unit comprising:

a microprocessor;

a system bus connected to said microprocessor;

an embedded Flash memory comprising a code port and a data port connected to said system bus for interfacing with said microprocessor, and a field programmable gate array (FPGA) port, said embedded Flash memory comprising four modules, each module being arranged in at least three programmable user-defined partitions, with each partition being dedicated to a corresponding port;

a direct memory access (DMA) channel connected to said system bus and to the FPGA port of said embedded Flash memory;
and

an embedded FPGA ~~for FPGA reconfigurations and~~ comprising an FPGA programming interface connected to said DMA channel for interfacing with the FPGA port of said Flash memory.

20. (Previously Presented) A reconfigurable processing unit according to Claim 19, wherein said microprocessor, said

In re Patent Application of:

BORGATTI ET AL.

Serial No. **10/798,401**

Filed: **JANUARY 30, 2004**

embedded Flash memory, said DMA channel and said embedded FPGA are integrated as a single chip.

21. (Currently Amended) A reconfigurable processing unit according to Claim 19, wherein said embedded FPGA comprises an SRAM ~~S-RAM~~ embedded FPGA.

22. (Previously Presented) A reconfigurable processing unit according to Claim 19, wherein said embedded Flash memory comprises:

a modular array structure comprising N memory modules;

a power memory arbiter (PMA); and

a charge pump connected to said PMA and being shared among said N memory modules.

23. (Previously Presented) A reconfigurable processing unit according to Claim 19, further comprising coprocessors connected to said system bus; wherein said embedded FPGA comprises:

an instruction extension interface for extending a datapath of said microprocessor for supporting a set of additional microprocessor instructions;

a master/slave interface for supporting said coprocessors; and

an input/output interface for interfacing with external units or sensors with application-specific communication

In re Patent Application of:
BORGATTI ET AL.
Serial No. **10/798,401**
Filed: **JANUARY 30, 2004**

protocols.

24. (Previously Presented) A reconfigurable processing unit according to Claim 19, wherein the code port of said embedded Flash memory is for optimizing random access time and an application system supported by the reconfigurable processing unit; the data port of said embedded Flash memory is for allowing access to application data for modification thereof; and the FPGA port of said embedded Flash memory is for providing serial access for downloading bit-streams for an embedded FPGA configuration.

25. (Previously Presented) A reconfigurable processing unit according to Claim 19, wherein the FPGA port of said embedded Flash memory comprises four configuration registers replicating information stored in the code port to be used for writing data for embedded FPGA configurations.

26. (Previously Presented) A reconfigurable processing unit according to Claim 24, wherein the FPGA port uses a chip select signal to access addressable memory space, and a burst enable signal to allow burst serial access.

Claim 27 (Canceled).

28. (Currently Amended) A method for making a reconfigurable processing unit comprising:

In re Patent Application of:
BORGATTI ET AL.
Serial No. **10/798,401**
Filed: **JANUARY 30, 2004**

connecting a microprocessor and at least one
coprocessor to a system bus;

connecting a code port and a data port of an embedded
Flash memory to the system bus for interfacing with the
microprocessor, the embedded Flash memory also comprising a field
programmable gate array (FPGA) port;

connecting a direct memory access (DMA) channel to the
system bus and to the FPGA port of the embedded Flash memory; and

connecting an FPGA programming interface of an embedded
FPGA ~~for FPGA reconfigurations~~ to the DMA channel for interfacing
with the FPGA port of the embedded Flash memory, the embedded
FPGA comprising an instruction extension interface for extending
a datapath of the microprocessor for supporting a set of
additional microprocessor instructions, a master/slave interface
for supporting the at least one coprocessor, and an input/output
interface for interfacing with external sensors with application-
specific communication protocols.

29. (Currently Amended) A method according to Claim
28, wherein the microprocessor, the at least one coprocessor, the
system bus, the embedded Flash memory, the DMA channel and the
embedded FPGA are integrated as a single chip.

30. (Currently Amended) A method according to Claim
28, wherein the embedded FPGA comprises an SRAM ~~S-RAM~~ embedded
FPGA.

In re Patent Application of:
BORGATTI ET AL.
Serial No. 10/798,401
Filed: **JANUARY 30, 2004**

31. (Previously Presented) A method according to Claim 28, wherein the embedded Flash memory comprises a modular array structure comprising N memory modules, a power memory arbiter (PMA), and a charge pump connected to the PMA and being shared among the N memory modules.

Claim 32 (Cancelled).

33. (Previously Presented) A method according to Claim 28, wherein the code port of the embedded Flash memory is for optimizing random access time and an application system supported by the reconfigurable processing unit; the data port of the embedded Flash memory is for allowing access to application data for modification thereof; and the FPGA port of the embedded Flash memory is for providing serial access for downloading bit-streams for an embedded FPGA configuration.

34. (Previously Presented) A method according to Claim 28, wherein the FPGA port of the embedded Flash memory comprises four configuration registers replicating information stored in the code port to be used for writing data for embedded FPGA configurations.

35. (Previously Presented) A method according to Claim 33, wherein the FPGA port uses a chip select signal to access

In re Patent Application of:
BORGATTI ET AL.
Serial No. **10/798,401**
Filed: **JANUARY 30, 2004**

addressable memory space, and a burst enable signal to allow burst serial access.

36. (Previously Presented) A method according to Claim 28, wherein the embedded Flash memory comprises four modules, each module being arranged in at least three programmable user-defined partitions, with each partition being dedicated to a corresponding port.

37. (New) A method for making a reconfigurable processing unit comprising:

connecting a microprocessor to a system bus;

connecting a code port and a data port of an embedded Flash memory to the system bus for interfacing with the microprocessor, the embedded Flash memory also comprising a field programmable gate array (FPGA) port and four modules, with each module being arranged in at least three programmable user-defined partitions, and with each partition being dedicated to a corresponding port;

connecting a direct memory access (DMA) channel to the system bus and to the FPGA port of the embedded Flash memory; and

connecting an FPGA programming interface of an embedded FPGA to the DMA channel for interfacing with the FPGA port of the embedded Flash memory.

In re Patent Application of:
BORGATTI ET AL.
Serial No. **10/798,401**
Filed: **JANUARY 30, 2004**

38. (New) A method according to Claim 37, wherein the microprocessor, the embedded Flash memory, the DMA channel and the embedded FPGA are integrated as a single chip.

39. (New) A method according to Claim 37, wherein the embedded FPGA comprises an SRAM embedded FPGA.

40. (New) A method according to Claim 37, wherein the embedded Flash memory comprises a modular array structure comprising N memory modules, a power memory arbiter (PMA), and a charge pump connected to the PMA and being shared among the N memory modules.

41. (New) A method according to Claim 37, further comprising connecting coprocessors to the system bus; wherein the embedded FPGA comprises:

an instruction extension interface for extending a datapath of said microprocessor for supporting a set of additional microprocessor instructions;

a master/slave interface for supporting the coprocessors; and

an input/output interface for interfacing with external units or sensors with application-specific communication protocols.

42. (New) A method according to Claim 37, wherein the code port of the embedded Flash memory is for optimizing random

In re Patent Application of:

BORGATTI ET AL.

Serial No. **10/798,401**

Filed: **JANUARY 30, 2004**

access time and an application system supported by the reconfigurable processing unit; the data port of the embedded Flash memory is for allowing access to application data for modification thereof; and the FPGA port of the embedded Flash memory is for providing serial access for downloading bit-streams for an embedded FPGA configuration.

43. (New) A method according to Claim 37, wherein the FPGA port of the embedded Flash memory comprises four configuration registers replicating information stored in the code port to be used for writing data for embedded FPGA configurations.

44. (New) A method according to Claim 42, wherein the FPGA port uses a chip select signal to access addressable memory space, and a burst enable signal to allow burst serial access.